



AMERICAN PETROLEUM INSTITUTE

---

# API Standard 527

## Seat Tightness of Pressure Relief Valves

FOURTH EDITION | NOVEMBER 2014 | 5 PAGES | \$90.00 | PRODUCT NO. C52704

---

This standard describes methods of determining the seat tightness of metal- and soft-seated pressure relief valves, including those of conventional, bellows, and pilot-operated designs.

The maximum acceptable leakage rates are defined for pressure relief valves with set pressures from 103 kPa gauge (15 psig) to 41,379 kPa gauge (6000 psig). If greater seat tightness is required, the purchaser shall specify it in the purchase order.

The test medium for determining the seat tightness—air, steam, or water—shall be the same as that used for determining the set pressure of the valve.

For dual-service valves, the test medium—air, steam, or water—shall be the same as the primary relieving medium.

To ensure safety, the procedures outlined in this standard shall be performed by persons experienced in the use and functions of pressure relief valves.

For ordering information:

Online: [www.api.org/pubs](http://www.api.org/pubs)

Phone: 1-800-854-7179  
(Toll-free in the U.S. and Canada)

(+1) 303-397-7056  
(Local and International)

Fax: (+1) 303-397-2740

API members receive a 30% discount where applicable.

## Contents

	Page
<b>1 Scope</b> .....	<b>1</b>
<b>2 Testing with Air</b> .....	<b>1</b>
<b>2.1 Test Apparatus</b> .....	<b>1</b>
<b>2.2 Procedure</b> .....	<b>2</b>
<b>2.3 Acceptance Criteria</b> .....	<b>3</b>
<b>3 Testing with Steam</b> .....	<b>3</b>
<b>3.1 Procedure</b> .....	<b>3</b>
<b>3.2 Acceptance Criteria</b> .....	<b>4</b>
<b>4 Testing with Water</b> .....	<b>4</b>
<b>4.1 Procedure</b> .....	<b>4</b>
<b>4.2 Acceptance Criteria</b> .....	<b>4</b>
<b>5 Testing with Air—Another Method</b> .....	<b>4</b>
<b>5.1 Type of Valve to be Tested</b> .....	<b>4</b>
<b>5.2 Procedure</b> .....	<b>5</b>
<b>5.3 Acceptance Criteria</b> .....	<b>5</b>
<b>Figures</b>	
<b>1 Apparatus to Test Seat Tightness with Air</b> .....	<b>1</b>
<b>2 Device to Relieve Body Pressure Caused by Accidental Popping of the Valve</b> .....	<b>2</b>
<b>Table</b>	
<b>1 Maximum Seat Leakage Rates for Metal-Seated Pressure Relief Valves</b> .....	<b>3</b>