



2" TO 18" 手轮操作
20" TO 24" 齿轮箱操作



8	LOCK NUT	BRASS	1						
7	STEM	SS304	1						
6	PACKING GLAND	SS304	1						
5	PACKING	PTFE	3						
4	RETAINER	SS304	1						
3	GATE	SS304	1						
2	SEAT	NBR	1						
1	BODY	SS304	1						
NO.	PARTS NAME	MATERIAL	QTY						
TEST PRESSURE	SHELL		SEAL						
		2"-10"	12"-16"	18"-24"	2"-10"	12"-16"	18"-24"		
	HYDROSTATIC	15 BAR	10.5 BAR	6 BAR	10 BAR	7 BAR	4 BAR		
STAND-ARD	DESIGN CODE		API 598						
	INSPECTION & TEST		ANSI B16.5						
	END STANDARD		API 609						
	FACE TO FACE								
SIZE		HA	HB	HC	L	T	Tr	φC	n-M (FLANGE)
DN	Inch								
50	2"	65	289	153	40	5	Tr20x4	120.5	4-5/8"-11
65	2.5"	70	313	172	40			139.5	
80	3"	95	335	182	50			152.5	
100	4"	108	380	215	50	6	Tr20x4	190.5	8-5/8"-11
125	5"	124	415	235	50			216	
150	6"	135	470	260	60	8	Tr25x5	241.5	8-3/4"-10
200	8"	165	580	325	60			298.5	
250	10"	198	670	386	70	10	Tr25x5	362	12-7/8"-9
300	12"	234	768	430	80			432	
350	14"	256	900	486	96	12	Tr35x6	476	12-1"-8
400	16"	292	1014	525	100			539.5	16-1"-8
450	18"	308	1127	585	106	14	Tr40x7	578	16-1 1/8"-7
500	20"	440	1310	634	620			635	20-1 1/8"-7
600	24"	510	1595	678	725	14	Tr40x7	749.5	20-1 1/4"-7