



SIDE	A	B	C	E	F	H	I	J	K	L	N	Ø
2"	50	57.15	60.3	15.88	7.93	119	63	90	30	82.4	70	9
2.5"	61	69.09	73	15.88	7.93	125.5	68.5	90	30	96.8	70	9
3"	80	84.94	88.9	15.88	7.93	131.5	80	90	30	96.8	70	9
4"	101	110.08	114.3	15.88	9.53	151	94	90	30	115.8	70	9
5"	127	137.03	141.3	15.88	9.53	171.5	108	90	30	147.6	70	9
6"	150	163.96	168.3	15.88	9.53	183	123	90	30	147.6	70	9
8"	202	214.4	219.1	19.05	11.1	205.4	149.4	125	40	133.4	102	11
10"	253	268.28	273	19.05	12.7	250	186	125	40	158.8	102	11
12"	303	318.29	323.9	19.05	12.7	275	213	125	40	163.6	102	11

5	DISC	DI+EPDM	1
4	BODY	CI	1
3	STEM	SS410	1
2	X-RING	NBR	1
1	BUSHING	PTFE	1
NO.	PARTS NAME	MATERIAL	QTY

TEST PRESSURE	SHELL		SEAL
	HYDROSTATIC	24 Kg/cm ²	17.6 Kg/cm ²
AIR			

STAND-ARD	DESIGN CODE	BS
-----------	-------------	----

TITLE : Signal gear Grooved End Butterfly Valve
DN50-DN300

APPROVED		DWG NO.	REV
CHECKED			
DRAWN			
DESIGNED		SCALE	UNIT
			mm